

Project : Installation Gaudi software on LG webOS 2.0 monitor
 Version : 3
 Date : 27-6-2017

Step 1: Setup your LG webOS monitor

If this is the first time you use the LG webOS monitor, you will need to carry out the following steps.

Turn on your monitor

1. To begin with the setup use the remote to turn on the LG monitor wait for it to fully power on.
2. First you'll have to select a language and country, but because of the Factory Reset you have to perform in step 2 leave the prefilled settings the way they are. Click **OK**.
3. In the Rotation menu click on; **leave the TV option for first use**.

Factory Reset

1. Then press and hold the **Settings** button on the remote control until a small box with a chat bubble icon appears in the top-right corner.
2. Once you can see the chat bubble icon, please press quickly the following **0, 0, 0, 0** and **OK** key sequence on your remote control, to open the **Signage Setup** menu.
3. Press the **right arrow** button to select Signage Setup. Use the **down arrow** button go to the bottom of the list and select **Factory Reset**. Confirm the factory reset option and the LG monitor will turn off.

Monitor First Use setup

1. Turn the LG monitor back on and wait for it to fully power on.
2. Set your preferred language and your location, by choosing your continent and country. A time zone will be selected automatically.
3. If the monitor will be used in portrait mode, you can change "OSD Portrait Mode". Please do not change "Content Rotation".
4. Set your internet connection. It is preferable to use a wired connection.
5. On/Off timer: Please do not use this On/Off timer. You can manage the power on and power off in the Gaudi CMS.
6. Then press and hold the **Settings** button on the remote control until a small box with a chat bubble icon appears in the top-right corner.
7. Once you can see the chat bubble icon, please press quickly the following **0, 0, 0, 0** and **OK** key sequence on your remote control, to open the **Signage Setup** menu.
8. Press the **right arrow** button to select **Signage Setup**. Then set **Power Modus** to **PWR**, use the **down arrow** button and set **Auto Power Off** to **Off** and finally set **DPM** to **Off**.
9. Congratulations! Your LG webOS monitor is now ready for the Gaudi software. To do this please go to the next step.

